## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUX	XRAM
------------------------------------	------

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model	identifier:	1910053
IVIUUEI	idelitillei.	TATOOSS

Tyne	οf	liσht	sourc	۵.
IVDE	UI.	HEIIL	Souit	┖.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G13		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Froduct parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
0,	mption in on- 00 h), rounded st integer	18	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	2 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	18,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without separate control gear, lighting control	Height Width Depth	1 212 26 26	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	162	
		Chromaticity coordinates (x and y)	0,380 0,380	
Parameters for LED and OLED li	ght sources:			
R9 colour rendering index value	4	Survival factor	0,95	
the lumen maintenance factor	0,80			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	3	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)'-': not applicable; (b)'-': not applicable;

## Spectrum

