Product Information Sheet

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | | | _ | |
|--|------------------|---------------------------|--|---------------|
| Supplier's name | e or trade mark: | TECHTOUCH | | |
| Supplier's addre | ess: INTERLUSA, | Estr. interior da ciro | cunvalação 12477, 4100- | 178 Porto, PT |
| Model identifie | r: 2500021 | | | |
| Type of light so | urce: | | | |
| Lighting techno | logy used: | LED | Non-directional or directional: | NDLS |
| Light source cap | o-type | N/A | | |
| (or other electri | ic interface) | | | |
| Mains or non-m | nains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable | e light source: | No | Envelope: | - |
| High luminance | light source: | No | | |
| Anti-glare shield | d: | No | Dimmable: | No |
| | | Product para | | T - |
| Parameter | | Value | Parameter | Value |
| | | General product | 1 | I |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 10 | Energy efficiency class | F |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 1 000 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P _{on}), ex- pressed in W | | 10,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| Outer dimen- | Height | 1 000 | Spectral power dis- | See image |
| Atlanta of the con- | | | T. 1.21. 12 | 1 |

tribution

8

2

in

range 250 nm to 800

nm, at full-load

the

in last page

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | | |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordi- | 0,403 | | | |
| | | nates (x and y) | 0,440 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 3 | Survival factor | 0,95 | | | |
| the lumen maintenance factor | 0,80 | | | | | |

(a)'-': not applicable; (b)'-': not applicable;

Spectrum

