Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUXRAM

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model identifier: 706155291

Type of light source:

Colour tupophia light courses	No	Connected light source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
•.	mption in on- 100 h), rounded st integer	28	Energy efficiency class	F			
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 950 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400			
On-mode p expressed in W	oower (P _{on}),	28,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
for CLS, expre	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer dimensions without	Height	1 212	Spectral power	See image			
	Width	26	distribution in the	in last page			
	Depth	26	1	Page 1/3			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	175			
		Chromaticity coordinates (x and y)	0,312 0,335			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-26	Survival factor	0,95			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	1			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-' : not applicable;

(b)'_-' : not applicable;

