Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLOAILD KLOOI	-A11014 (L0) 2013/2	015 with regard to energ	gy labelling of light		
Supplier's name	e or trade mark:	LUXRAM				
Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT						
Model identifie	er: 764181021					
Type of light so	urce:					
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap (or other electri	• •	G13				
Mains or non-m	nains:	MLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance		No				
Anti-glare shield	d:	No	Dimmable:	No		
		Product para		T		
Parameter		Value	Parameter	Value		
		General product p				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		820 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400		
On-mode power (P _{on}), expressed in W		9,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	612	Spectral power	See image		
dimensions	Width	26	distribution in the	in last page		
without	Depth	26		Page 1 /		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	61			
		Chromaticity	0,311			
		coordinates (x and y)	0,336			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-25	Survival factor	0,95			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	1			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

