# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: LUXRAM

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

#### Model identifier: 764181082

### Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	G13					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

		i iouuci paia					
Parameter		Value	Parameter	Value			
General product parameters:							
	nption in on- 00 h), rounded st integer	22	Energy efficiency class	F			
indicating if it re in a sphere (36	us flux (фuse), efers to the flux 50º), in a wide n a narrow cone	2 300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode p expressed in W	ower (P <sub>on</sub> ),	22,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked stan for CLS, expres rounded to the		-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer dimensions without	Height	1 512	Spectral power	See image			
	Width	26	distribution in the	in last page			
	Depth	26	-				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	142			
		Chromaticity coordinates (x and y)	0,378 0,375			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-16	Survival factor	0,95			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	2			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

## Spectrum

