Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUXRAM

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model identifier: 770411143

Type of light source:

Product parameters						
Anti-glare shield:	No	Dimmable:	Yes			
High luminance light source:	No					
Colour-tuneable light source:	No	Envelope:	-			
Mains or non-mains:	MLS	Connected light source (CLS):	No			
(or other electric interface)						
Light source cap-type	E14					
Lighting technology used:	LED	Non-directional or directional:	NDLS			

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 00 h), rounded st integer	4	Energy efficiency class	E		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	470 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pow pressed in W	ver (P _{on}), ex-	4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
(P_{net}) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen- sions without separate con- trol gear, light- ing control	Height	100	Spectral power dis- tribution in the range 250 nm to 800 nm, at full-load	See image		
	Width	35		in last page		
	Depth	35		Dage 1		

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	40				
		Chromaticity coordi- nates (x and y)	0,380 0,380				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	3	Survival factor	0,95				
the lumen maintenance factor	0,80						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	3				
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-				
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4				

(a)_{'-'} : not applicable;

(b)'_-' : not applicable;



