Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	PELEGATED REGUL	-ATION (EU) 2019/20	DIS with regard to energ	gy labelling of light		
Supplier's name	e or trade mark:	LUXRAM				
Supplier's address: Rui Müller, Estrada interior da Circunvalação nº 12477, 4100-178 Porto, PT						
Model identifie	r: 779114042					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		E14				
(or other electric interface)						
Mains or non-mains:		MLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
Product parameters						
Parameter Value Parameter Value General product parameters:						
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		7 650 in Sphere (360°)	Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour	F 4 000		
			temperatures, rounded to the nearest 100 K, that can be set			
On-mode power (P _{on}), expressed in W		6,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	100	Spectral power	See image		
dimensions without	Width	37	distribution in the	in last page		
without	Depth	37		 Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	51			
		Chromaticity	0,387			
		coordinates (x and y)	0,386			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	7	Survival factor	0,95			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

