Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LUMIT

Supplier's address: INTERLUSA, Estr. interior da circunvalação 12477, 4100-178 Porto, PT

Model identifier: A065805I1A

Type of light sou

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	N/A		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	No

Product parameters

Froduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
0,	mption in on- 00 h), rounded st integer	5	Energy efficiency class	F		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	450 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P _{on}), ex-	5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-		
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimensions without separate control gear, lighting control	Height Width	35 22	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page		
	Depth	300				

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,423 0,389		
Parameters for	Parameters for LED and OLED light sources:					
R9 colour rende	ring index value	-22	Survival factor	1,00		
the lumen main	tenance factor	-				
Parameters for LED and OLED mains light sources:						
displacement fa	ctor (cos φ1)	0,80	Colour consistency in McAdam ellipses	2		
replaces a flu	LED light source uorescent light integrated balar wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (F	Pst LM)	0,1	Stroboscopic effect metric (SVM)	-		

(a)'-': not applicable; (b)'-': not applicable;

