Product Information Sheet

COMMISSION DELEGATED REGULATION (ELL) 2019/2015 with regard to energy labelling of light

commission D sources	ELEGATED REGUI	ATION (EU) 2019/2	015 with regard to ener	gy labelling of light
Supplier's name	e or trade mark:	LUMIT		
Supplier's addre	ess: INTERLUSA,	Estr. interior da circ	unvalação 12477, 4100-	178 Porto, PT
Model identifie	r: A065809I1B			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		N/A		
(or other electric interface)				
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		Yes	Dimmable:	No
		Product para		I
Parameter		Value	Parameter	Value
		General product p		_
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		810 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), ex- pressed in W		9,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	35	Spectral power dis-	See image
sions without separate con- trol gear, light- ing control	Width Depth	22 568	tribution in the range 250 nm to 800 nm, at full-load	in last page

parts and non- lighting con- trol parts, if any (millime-						
tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,371			
		nates (x and y)	0,377			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	ue 21	Survival factor	-			
the lumen maintenance facto	r -					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,80	Colour consistency in McAdam ellipses	2			
Claims that an LED light sour replaces a fluorescent lig source without integrated by last of a particular wattage.	ht	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	-			

(a)'-': not applicable; (b)'-': not applicable;

